

TECHNICAL DATA SHEET



GO! T Series

	GO! T1.5	GO! T2.5	GO! T2.6(+)
Maximum speed	45 kph	45 kph	45 kph (63 kph for the '+' Version)
Range	40-60 km	60-90 km	90-120 km
Brakes	Front and rear hydraulic disc brake	Front and rear hydraulic disc brake	Front and rear hydraulic disc brake
Tires	130/60-R13 front and rear	130/60-R13 front and rear	130/60-R13 front and rear
Front Fork	Hydraulic telescope fork	Hydraulic telescope fork	Hydraulic telescope fork
Rear suspension	Mono shock absorber	Mono shock absorber	Mono shock absorber
Battery	Lithium-ion	Lithium-ion	Lithium-ion
Voltage	72 Volt	72 Volt	72 Volt
Weight battery	16 kg	32 kg	32 kg
Battery (estimated lifetime)	50.000 km	50.000 km	50.000 km
Charger	600 W, on board 110/240 V (50/60 Hz)	1000 W, on board 110/240 V (50/60 Hz)	1000 W, on board 110/240 V (50/60 Hz)
Charging time	2-3 h, 80% in 1h	4-5 h, 80% in 2h	5-6 h, 80% in 2h
Motor	Brushless motor, PMAC with belt drive	Brushless motor, PMAC with belt drive	Brushless motor, PMAC with belt drive
Torque	54 Nm	54 Nm	54 Nm
Weight	Approx. 104kg (incl. battery)	Approx. 123 kg (incl. battery)	Approx. 122 kg (incl. battery)
Wheelbase	1335 mm	1335 mm	1335 mm
Seat height	790 mm	790 mm	790 mm
Storage capacity	more than 200 l / 100 kg	more than 200 l / 100 kg	more than 200 l / 100 kg
Carrying capacity	180 kg	180 kg	180 kg
Guarantee	24 month	24 month	24 month
Emissions	Zero	Zero	Zero